



Available only from the technology experts at SMART PARK

- **Designed for Commercial and Industrial Applications**
- **3 Switchable Viewing Angles.**
- **Calibrated to suit a full range of mounting heights**
- **High Resolution Megapixel Imager**
- **Heavy Duty Metal Waterproof Housing**
- **Camera with inbuilt Microphone**
- **Very High Dynamic Range Imager for high contrast environments.**
- **Three Year Warranty**
- **Hibrite LED lighting for great low light performance in all conditions.**
- **Using the highest quality OEM grade components for reliability and durability.**

| Specifications | CAM150MV |
|-----------------------------|---------------------------------------|
| Dimension (mm) | 82 (L) x 73 (W) x 58 (D) mm |
| Image Sensor | 1/2.7" OV10635 Digital |
| Lens | Focal Length 1.78mm Max Aperture F2.0 |
| View angle (Horizontal) | 180° |
| View angle (Vertical) | 190 |
| IR LED | Yes (On/Off) |
| Microphone | Yes |
| Power Requirements | DC 12V |
| Power consumption | 1.2W |
| Mirror control | Yes |
| Video format | NTSC |
| Video signal output | 1 Vp-p (75ohm) |
| Effective Pixel Resolution | NTSC 720 x 480 |
| S/N (dB) | <39 Db |
| Illumination (min.) | 0 Lux With IR LED (ON/OFF) |
| Additional Specifications | Automatic Exposure/Gain Control |
| Self diagnostic controller | Auto White Balance |
| | Aperture & Gamma Correction |
| Waterproof and dustproof | IP69K |
| Operating Temperature Range | -30°C ~ +85 °C RH95% Max |
| Storage temperature | -40°C~+105°C RH95% Max |
| Weight | (Including Mounting Bracket)144g |
| Guide Line | Yes |