



Features of LCD704WHD

- 7" LCD colour monitor with HD 1280 x 720P high resolution display
- Expandable 4/2/1 channel camera input
- Wireless range of up to 400m transmission distance (line of sight)
- Automatic pairing function of monitor & camera(s)
- Night-vision function (6pcs white LED)
- 7" monitor with inbuilt DVR
- SD card data storage
- Quad, split or single screen display
- Mirror and normal image switch available
- Programmable parking guidelines
- Built-in microphone and sound capability
- Wide voltage input: DC 9V – 36V
- Waterproof: IP68
- Vibration: 10G
- Two year warranty

Specifications for LCD704WHD

Image (Main Chip)	7.0" LCD monitor
Transmission Frequency	2.4G (digital)
Transmission Resolution	High definition
Transmission Delay (Ave)	150ms
RF Pairing	Auto
Changeable Channel	125 CH (overlapping hopping channel)
Voltage	DC9 – 36V
Consumption	< 5W
Brightness	350cdm
Mirror Image	Yes (via menu select)
Speaker	Yes
Contrast / Brightness	Yes
Camera Selection	1-4 (auto or manual)
Dimensions	185W x 128H x 26D mm
Weight	400g
Temperature	-20°C to +70°C



Features of CAM150WHD

- HD720P high resolution, super wide angle lens
- Wireless range of up to 400m transmission distance (line of sight)
- Automatic pairing function of monitor & camera(s)
- Night-vision function (6pcs white LED)
- Mirror and normal image switchable
- Built-in microphone
- Wide voltage input: 9V ~ 36V system
- Waterproof: IP68
- Vibration: 10G
- Firm structure: aluminium-alloy housing, anti-UV surface painting
- Angle adjustable
- Two year warranty

Specifications for CAM150WHD

Image (Main Chip)	1/3.7" CMOS BSI color 1280H x 960V pixels
Voltage	DC9 ~ 36V
Consumption	< 1W
Lens Angle	130° diagonal
Microphone	Yes
White LED Switch Control	Photo sensor automatic control
Infrared LEDs	6 (10m visibility)
Housing	Aluminium alloy
Mechanical Vibration	10G
Mounting	Permanent tilt bracket
Dimensions	93W x 83.5H x 57D mm
Weight	272g
Temperature	-40°C to +85°C
Ingress Protection	IP68