



## Features

- High resolution LCD monitor
- Expandable 3 channel camera input
- Heavy duty U shape mounting bracket
- Sony CCD image sensor
- IR night vision capability
- Remote control included
- Mirror and normal image switch function
- Programmable parking guidelines
- Built-in microphone and sound capability
- Wide voltage input: DC 10V – 32V
- Waterproof camera: IP69K
- Complete plug and play solution
- Two year warranty

## Specifications for LCD503

Housing Colour	Black
Display Size	5 inch
Type of Display	TFT
Camera Inputs	3 AV input
Standard (PAL/NTSC)	Yes
Auto Detect	Yes
Video Output	CVBS signal
Standard (PAL/NTSC)	Yes
Resolution	800*RGB*480
Brightness	350cd/m2
Guidelines	Yes
Mirror Function (V/H)	Yes
Picture Adjustable	Yes
Loudspeaker	Yes
Menu Languages	English, Simplified Chinese
Remote Control	Yes
Operating Voltage	DC10-32V
Current Consumption	5W
Cable Length at Monitor	30cm
Operating Temperature	-20°C ~ +70°C
Storage Temperature	-30°C ~ +80°C
Housing Material	ABS
Trigger	3
Bracket	U bracket
Sunshade	Removable

## Specifications for CAM155

Housing Colour	Black
Image Sensor	SONY
Type (CMOS/CCD)	CCD
Resolution	700TVL
Viewing Angle (V/H/D)	D/150°
Standard (PAL/NTSC)	NTSC
IR Illumination	Yes
Light Sensitivity	AUTO
Backlight Compensation	AUTO
White Balance	AUTO
Mirror Function	Mirror
Operating Voltage	12V
Cable Length at Camera	30cm
Operating Temperature	-20°C ~ +70°C
Storage Temperature	-30°C ~ +80°C
Protection Class	IP69K
Audio	YES
Mechanical Vibration	4G
Housing Material	Aluminium alloy